



**NOTA :**  
 Prévoir 6 clips CO3 pour L 2 mètres  
 Allow 6 CO3 cover clips for 2 meters



www.niedaxfrance.fr

Description	Code	Masse/Weight Kg/ml	Ep./Th. mm	l./w. mm
CO2 51 I3	205201	0,458	0,80	52,60
CO2 75 I3	205202	0,610	0,80	76,60
CO2 99 I3	205203	0,763	0,80	100,60
CO2 123 I3	205204	0,916	0,80	124,60
CO2 147 I3	205205	1,068	0,80	148,60
CO2 171 I3	205206	1,221	0,80	172,60
CO2 195 I3	205207	1,374	0,80	196,60
CO2 220 I3	205208	1,530	0,80	221,60
CO2 268 I3	205210	1,832	0,80	269,60
CO2 316 I3	205212	2,137	0,80	317,60
CO2 364 I3	205214	2,44	0,80	365,60
CO2 412 I3	205216	2,747	0,80	413,60
CO2 460 I3	205218	3,053	0,80	461,60
CO2 508 I3	205220	3,36	0,80	509,60
CO2 532 I3	205221	3,51	0,80	533,60
CO2 604 I3	205224	4,96	1	606

SS316L : X2CrNiMo17-12-2 stainless steel wire according to NF EN 10088-3  
 I3 : Tôle d'acier inoxydable suivant NF EN 10088-2 (316L).

<b>COUVERCLE CO2 I3</b> <b>CO2 TRAY COVER SS316L</b>		
ASSISTANCE TECHNIQUE +33 (0)1 55 95 92 17 pole.technique@niedax.fr		
<b>FT03242</b>		