



Description	Code	Masse/Weight Kg/p	Ep./Th. mm	H mm	l./w. mm
Virage 135 D GRS 48x 48 I3	230040	0,591	1,00	50	50
Virage 135 D GRS 72x 48 I3	-	0,713	1,00	50	74
Virage 135 D GRS 96x 48 I3	230042	0,825	1,00	50	98
Virage 135 D GRS 120x 48 I3	230043	0,958	1,00	50	122
Virage 135 D GRS 144x 48 I3	-	1,090	1,00	50	146
Virage 135 D GRS 192x 48 I3	-	1,386	1,00	50	194
Virage 135 D GRS 312x 48 I3	-	2,222	1,00	50	314
Virage 135 D GRS 408x 48 I3	-	3,404	1,00	50	410
Virage 135 D GRS 504x 48 I3	-	4,443	1,00	50	506

I3 : Tôle d'acier inoxydable suivant NF EN 10088-2 (316L).
 SS316L : Stainless steel according to NF EN 10088-2 (316L).

VIRAGE 135 D GRS + CO 48 I3
 H 135°BEND GRS 48 SS316L + COV



ASSISTANCE TECHNIQUE
 +33 (0)1 55 95 92 17
 pole.technique@niedax.fr

NIEDAX
 France



FT03287

www.niedaxfrance.fr